

## AMENDMENTS TO THE CLAIMS

### Listing of Claims:

The listing of claims will replace all prior versions, and listings of claims in the application.

1. (Currently amended) A system for applying compression therapy to patient's limb, the system comprising
  - a patient-support apparatus having a module-receiving cavity provided within a first portion of the patient support apparatus, the patient-support apparatus having a base above which the first portion is located and relative to which the first portion is raiseable and lowerable,
  - a compression sleeve adapted to couple to the patient's limb, the sleeve being inflatable to compress the patient's limb,
  - a conduit through which the sleeve is inflated,
  - a pneumatic coupler provided on a second portion of the patient-support apparatus that is spaced from the first portion of the patient support apparatus and that is accessible to a caregiver for selective and releasable connection of the compression sleeve to the pneumatic coupler, the conduit being routed through an interior region of the patient support apparatus between the module-receiving cavity and the pneumatic coupler, and
  - a compression module removably attachable to the patient-support apparatus and operable to inflate the compression sleeve through the conduit and the pneumatic coupler, at least a portion of the compression module being received in the module-receiving cavity such that an outlet port of the compression module pneumatically communicates with the conduit when the compression module is received within the module receiving cavity of the patient-support apparatus, the compression module being removable from the module-receiving cavity to permit the compression sleeve to be coupled to the compression module to permit the patient to ambulate away from the patient-support apparatus while wearing the compression sleeve and carrying the compression module, the conduit being left behind with the patient-support apparatus while the patient ambulates away from the patient-support apparatus, the compression module being operable to inflate the compression sleeve worn by the patient while the patient is ambulatory.

2. (Original) The system of claim 1, wherein the patient-support apparatus comprises a bed.

3. (Original) The system of claim 2, wherein the bed comprises a siderail and the module-receiving cavity is formed in the siderail.

4. (Previously presented) The system of claim 3, wherein at least a portion of the interior region of the patient-support apparatus comprises an interior region of the siderail and at least a portion of the conduit is situated in the interior region of the siderail.

5. (Original) The system of claim 2, wherein the bed comprises a footboard and the module-receiving cavity is formed in the footboard.

6. (Previously presented) The system of claim 5, wherein at least a portion of the interior region of the patient-support apparatus comprises an interior region of the footboard and at least a portion of the conduit is situated in the interior region of the footboard.

7. (Original) The system of claim 2, wherein the bed comprises a mattress and the module-receiving cavity is formed in the mattress.

8. (Previously presented) The system of claim 7, wherein at least a portion of the interior region of the patient-support apparatus comprises an interior region of the mattress and at least a portion of the conduit is situated in the interior region of the mattress.

9. (Original) The system of claim 2, wherein the bed comprises a patient-support deck and the module-receiving cavity is formed in the patient-support deck.

10. (Previously presented) The system of claim 9, wherein at least a portion of interior region of the patient-support apparatus comprises an interior region of the patient-support deck and at least a portion of the conduit is situated in the interior region of the patient-support deck.

11. (Original) The system of claim 9, wherein the patient-support deck has a first deck section and a second deck section, the first deck section is movable with respect to the second deck section, and the module-receiving cavity is formed in the first deck section.

12. (Currently amended) The system of claim 1, wherein the patient-support apparatus has an inlet port in pneumatic communication with the conduit[[,]] and the outlet port couples automatically to the inlet port when the compression module is inserted into the module-receiving cavity.

13. (Previously presented) The system of claim 1, wherein the compression module comprises an electric circuit and a pressure generator, the patient-support apparatus comprises an electrical system, and the electrical system of the patient-support apparatus communicates with the electric circuit of the compression module when the compression module is received in the module-receiving cavity.

14. (Original) The system of claim 13, wherein the compression module has a first electrical connector, the patient-support apparatus has a second electrical connector, and the first electrical connector mates automatically with the second electrical connector when the compression module is inserted into the module-receiving cavity.

15. (Original) The system of claim 13, wherein the electrical system comprises a user input device configured to receive user inputs to command the operation of the compression module and the user input device is spaced from the module-receiving cavity.

16. (Original) The system of claim 13, wherein the pressure generator comprises a pump.

17. (Original) The system of claim 13, wherein the pressure generator comprises a compressor.

18. (Original) The system of claim 1, wherein the compression module is adapted to receive pressurized fluid from an external source of pressurized fluid and the compression module comprises a first valve having an opened position allowing pressurized

fluid to flow through the conduit to inflate the compression sleeve and a closed position blocking the flow of pressurized fluid into the conduit.

19. (Original) The system of claim 1, wherein the patient-support apparatus comprises a mattress.

20. (Previously presented) The system of claim 19, wherein the mattress comprises a core and a coverlet in which the core is situated, the module-receiving cavity is formed in the core, and the coverlet has an opening through which the module-receiving cavity is accessed.

21. (Previously presented) The system of claim 20, wherein the interior region of the patient-support apparatus is provided within the coverlet, the conduit is routed at least partially through the interior region provided within the coverlet, and the pneumatic coupler is situated outside the interior region of the coverlet.

22. (Previously presented) The system of claim 21, wherein the pneumatic coupler is adjacent a side panel of the coverlet.

23. (Previously presented) The system of claim 22, wherein the pneumatic coupler is coupled to the side panel of the coverlet.

24. (Previously presented) The system of claim 23, wherein the coverlet has a top panel, a bottom panel, and the side panel extends between the top and bottom panels, and the pneumatic coupler is coupled to the side panel near a foot end of the mattress.

25. (Previously presented) The system of claim 23, wherein the coverlet and core have a head end, a foot end, and a pair of sides extending between the head and foot ends, the module-receiving cavity is closer to the head end than to the foot end, and the pneumatic coupler is closer to the foot end than to the head end.

26. (Original) The mattress of claim 20, further comprising a liner member having a first portion that lines the module-receiving cavity and having a second portion coupled to the coverlet.

27. (Original) The mattress of claim 26, wherein the first portion of the liner member has a space configured to receive at least a portion of the compression module therein.

28. (Original) The mattress of claim 26, wherein the second portion comprises a flange that couples to the coverlet adjacent the opening.

29.-104. (Cancelled)